

# Yes-Original

## IPC-ORB212P 1080P IR Bullet Network Camera



### Key Feature:

- H.265 encoding high compression
- 2.0 MP CMOS High-performance processor imaging sensor, 1080P@25fps realtime monitoring
- True Day/Night
- Support ONVIF
- Support POE
- Supports network interrupt, IP conflict, motion detection, video blind smart alarm
- Up to 35m IR distance

### Usage Scenarios:

Home, office, school, shopping mall, shops, restaurant, etc.



## Specifications

| Camera               |                                                                        |
|----------------------|------------------------------------------------------------------------|
| Image Sensor         | 2.0MP CMOS Image Sensor                                                |
| Signal System        | PAL/NTSC                                                               |
| Effective Pixels     | 1920*1080                                                              |
| Min. illumination    | 0.01Lux@ (F1.2, AGC ON), 0Lux with IR                                  |
| Shutter Time         | 1/25(1/30)s to 1/50,000s                                               |
| Lens                 | 3.6mm                                                                  |
|                      | Angle of View: 74.6°                                                   |
| Lens Mount           | M12                                                                    |
| Day & Night          | ICR                                                                    |
| Angle Adjustment     | Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°                       |
| Synchronization      | Internal synchronization                                               |
| Video Frame Rate     | 1080P@25fps                                                            |
| HD Video Output      | 1 Analog HD output                                                     |
| S/N Ratio            | >52dB                                                                  |
| General              |                                                                        |
| Operating Conditions | -20 °C - 45 °C (-4 °F - 113 °F), Humidity 90% or less (non-condensing) |
| Power Supply         | 12 VDC $\pm$ 10% /500mA                                                |
| Power Consumption    | Max.4W                                                                 |
| IR Range             | up to 35m                                                              |
| Dimensions           | $\Phi$ 154.6 x 71 mm                                                   |
| Weight               | 350g                                                                   |

# Yes-Original

## Dimensions

