

XVR 5 in 1

Yes-Original

OR16CH-5in1N 16CH 1080N 5 in 1 DVR



Key Feature:



App:Yes-Original



ios



android

- Support 16ch 1080N ;
- Support AHD, TVI,CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment;
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Mobile phone remote monitoring (iOS, Android);
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS Platform;

★ **NEW FUNCTION:** Support instant replay / U Disk backup / Snapshot/ Splice Play/ HDD Partition /Lock files/Free DDNS

System

Video Compression	H.264
Operating Systems	Embedded Linux
Video Input/Output	
Analog Video Input	16CH
Video Input interface	BNC(1.0Vp-p,75Ω),PAL/NTSC self-adaptive
IP Video Input	Up to 16-ch
HDMI/VGA Output	1*HDMI/VGA
CVBS Output	1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480

Record/Playback/Back up	
Record	16CH non-realtime
Record type	Regular,Manual,Detect,Alarm
Maximum Playback	16CH
Search ways	Point in time,Calendar,Event,Channel
USB Mobile hard disk,U disk	Support
Format	DAV AVI
Browser	IE/Firefox
Remote Control	
CMS	CMS3.0
Mobile Operating System	iPhone,Android
Hard disk	
Type	1SATA interface
Capacity	Up to 4 TB capacity for each disk
PTZ	
Interface	1*RS485
Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VIS CA,SAMSUNG,RM110,HY
Control ways	Pan, Tilt, Zoom, Preset, Cruise, Trace
Network	
Ethernet Interface	10/100 Mbs Ethernet(RJ-45)
Protocol	TCP/IP,DHCP,DDNS,NTP,SMTP
Remote Control	Support
Power Supply	12DC/2A
Consumption (without hard disk)	Max.10W
Working Temperature	-10°C ~+60°C
Working Humidity	10% ~ 90% Humidity

