

# XVR 5 in 1

# Yes-Original

## OR8CH-5in1 8MP H.265 8CH 8MP 5in1 DVR



App:Yes-Original



ios



android

### Key Feature:

- Support 8ch 8MP ;
- Support AHD, TVI,CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment;
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Mobile phone remote monitoring (iOS, Android);
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS Platform;

★ **NEW FUNCTION:** Support instant replay / U Disk backup / Snapshot/ Splice Play/ HDD Partition /Lock files/Free DDNS

### System

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Video Compression     | H.265                                                     |
| Operating Systems     | Embedded Linux                                            |
| Video Input/Output    |                                                           |
| Analog Video Input    | 8CH                                                       |
| Video Input interface | BNC(1.0Vp-p,75Ω),PAL/NTSC self-adaptive                   |
| IP Video Input        | Up to 8-ch                                                |
| HDMI/VGA Output       | 1*HDMI/VGA                                                |
| CVBS Output           | 1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480 |

| Record/Playback/Back up            |                                                                            |
|------------------------------------|----------------------------------------------------------------------------|
| Record                             | 8CH non-realtime                                                           |
| Record type                        | Regular,Manual,Detect,Alarm                                                |
| Maximum Playback                   | 4CH                                                                        |
| Search ways                        | Point in time,Calendar,Event,Channel                                       |
| USB Mobile hard disk,U disk        | Support                                                                    |
| Format                             | DAV AVI                                                                    |
| Browser                            | IE/Firefox                                                                 |
| Remote Control                     |                                                                            |
| CMS                                | CMS3.0                                                                     |
| Mobile Operating System            | iPhone,Android                                                             |
| Hard disk                          |                                                                            |
| Type                               | 1SATA interface                                                            |
| Capacity                           | Up to 6TB capacity for each disk                                           |
| PTZ                                |                                                                            |
| Interface                          | 1*RS485                                                                    |
| Protocol                           | PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VIS<br>CA,SAMSUNG,RM110,HY |
| Control ways                       | Pan, Tilt, Zoom, Preset, Cruise, Trace                                     |
| Network                            |                                                                            |
| Ethernet Interface                 | 10/100 Mbs Ethernet(RJ-45)                                                 |
| Protocol                           | TCP/IP,DHCP,DDNS,NTP,SMTP                                                  |
| Remote Control                     | Support                                                                    |
| Power Supply                       | 12DC/2A                                                                    |
| Consumption<br>(without hard disk) | Max.10W                                                                    |
| Working Temperature                | -10°C ~+60°C                                                               |
| Working Humidity                   | 10% ~ 90% Humidity                                                         |

